

=====
 Section I - IDENTIFICATION
 =====

Eutectic Canada Inc.
 428 Aimé-Vincent
 Vaudreuil-Dorion, Québec
 J7V 5V5

Emergency Telephone: (514) 695-7500

Product Name: Sealer 500
 AWS Standard Terminology: Air Drying Phenolic Coating
 WHMIS Classification: Other toxic effects

Transportation of Dangerous Goods: See section VIII

=====
 Section II - HAZARDOUS INGREDIENTS
 =====

Ingredient	Range wt%	CAS Number	Exposure Limit mg/m3
Mineral Spirits	40-70	64742-88-7	100 PPM

No other hazardous ingredients

=====
 Section III - PHYSICAL / CHEMICAL CHARACTERISTICS
 =====

The following data should only be used in the context of the Material Safety Data Sheet.

Physical State: Liquid
 Appearance: Clear
 Odour: Odorless
 Boiling Point: 150-210°C (300 - 410°F)
 Vapor Density (air = 1): > 1
 % Volatile / volume: 56
 Evaporation rate: < 1 (Ether = 1)
 Volume Weight: 7.3 lbs/gallon

=====
Section IV - FIRE AND EXPLOSION DATA
=====

Flammable: Yes, to open flame
Extinguishing media: Foam, Co2, dry chemical, water spray
Flash point: pmcc 40°C (104°F)
Upper explosive limit (% / volume): N/A
Lower explosive limit (%/volume): 1.0

=====
Section V - REACTIVITY
=====

Stable: Yes
Hazardous polymerization: Will not occur
Hazardous decomposition products: CO2, CO and hydrocarbons.

=====
Section VI - HEALTH HAZARD DATA
=====

Route of entry / exposure: Skin contact, eye contact, inhalation, ingestion.
Short and long term effects: Headaches, weakness, nervousness and nausea may result from inhalation - skin or eye contact may produce irritation.

=====
Section VII - EMERGENCY FIRST AID
=====

Skin, eyes, inhalation: Remove to well ventilated area. If skin / eyes contact - flush with water. Obtain medical assistance if necessary.

=====
Section VIII - PREVENTIVE MEASURES
=====

Personal equipment: Use CSA approved respirator for protection against fumes in confined areas. Wear protective goggles and chemical resistant gloves.
Storage and handling: Keep in a sealed container in a cool dry place. Keep away from open flame or excessive heat.
Spills: Remove all ignition sources. Absorb with an inert material.
Waste disposal method: Disposal should be in accordance with municipal and federal laws.
Transportation of Dangerous Goods: Combustible liquid N.O.S. (paint) UN 1993, Class 3.3, Packing Group III.

=====
Section IX - PREPARATION OF MATERIAL SAFETY DATA SHEET
=====

Prepared by: Director of Products and Services
Contact number: 514-695-7500
Date prepared: 30/09/99
Date revised: 30/09/2010 - Expiration Date: 30/09/2013